DELO® 100 MOTOR OILS

SAE 30, 40

PRODUCT DESCRIPTION

"The Delo® Performance Advantage™"

Delo® 100 Motor Oils are recommended for use in two- and four-stroke diesel engines in farm machinery, construction equipment, marine, and other off-highway applications where the SAE 30 or 40 grades are specified by the OEM.

CUSTOMER BENEFITS

Delo 100 Motor Oils are recommended for use in older two- and four-stroke diesel engines where the SAE 30 and/or 40 grades are specified by the OEM.

Delo 100 Motor Oils deliver value through:

- **Excellent high temperature deposit control** — Protects against high temperature oxidation and oil thickening in older engines.
- **Special extreme pressure antiwear properties** — Protect critical valve train wear points.
- **Protection against rust, corrosion, varnish, and sludge** — Helps keep oil screens, filters, and rings clean and free for prolonged periods.
- **Warranty Plus protection** — Bumper-to-bumper warranty protection from the engine to the drive train. Payment for Chevron lubricant-related damage to your equipment, including parts and labor.[1] Problem resolution and technical advice from Chevron's lubrication experts.
- **Access to Chevron's lubrication and industry knowledge** — Help maximize your bottom line business results.

FEATURES

Delo 100 Motor Oils are high performance crankcase oils for older diesel engines requiring a 30 or 40 monograde engine oil.

They are manufactured using selected premium paraffinic base oils and detergent, dispersant, wear control, antioxidant, corrosion inhibitor, and foam suppressant additives.

APPLICATIONS

Delo 100 Motor Oils are recommended for use in two- and four-stroke diesel engines in farm machinery, construction equipment, marine, and other off-highway applications where the SAE 30 or 40 grades are specified by the OEM. The SAE 30 and 40 grades are also specifically recommended for use in two-stroke diesel engines requiring highly effective control of wear and deposits.

Delo 100 Motor Oils utilize exceptional quality technology to provide excellent performance in older engines using either normal, high, or low sulfur diesel fuels.

Delo 100 Motor Oils meet the requirements of:

- **API CF Service Category**
- **API CF-2 Service Category**
- **Detroit Diesel Corporation two-stroke** engine recommendations, including the 0.85% ash maximum limit for Series 149 engines.

1 See Warranty Plus for details and restrictions.

Product(s) manufactured in the USA.
Always confirm that the product selected is consistent with the original equipment manufacturer's recommendation for the equipment operating conditions and customer's maintenance practices.

A **Chevron** company product

20 January 2011
HDMO-10

© 2007-2010 Chevron U.S.A. Inc. All rights reserved.
Chevron, the Chevron Hallmark, Delo and The Delo® Performance Advantage™ are trademarks owned by Chevron Intellectual Property LLC. All other trademarks are property of their respective owners.

TYPICAL TEST DATA

SAE Grade	30	40
Product Number	*222403*	*222404*
MSDS Number	*7329*	*7329*
API Gravity	28.1	27.7
Viscosity, Kinematic cSt at 40°C cSt at 100°C	 110 12.1	 152 15.0
Viscosity Index	99	99
Flash Point,°C(°F)	246(475)	258(498)
Pour Point, °C(°F)	-30(-22)	-27(-17)
Sulfated Ash, wt %	0.76	0.76
Base Number, ASTM D2896	7.3	7.3
Phosphorus, wt %	0.096	0.096
Zinc, wt %	0.105	0.105

Minor variations in product typical test data are to be expected in normal manufacturing.

Always confirm that the product selected is consistent with the original equipment manufacturer's recommendation for the equipment operating conditions and customer's maintenance practices.